



Outgassing data (ASTM Specification E595)

| Nelco / Neltec Product | Total Mass Loss TML (1% max) | Collected Volatiles Condensable Material CVCM (0.1% max) | Water Vapor Recovered WVR (No Limits) |
|---------------------------|---------------------------------|--|---|
| N4000-6 / 6FC | 0.27% | 0.06% | 0.006% |
| N4000-7 | 0.28% | 0.00% | 0.017% |
| N4000-11 | 0.11% | 0.004% | 0.07% |
| N4000-13 / 13SI | 0.37% | 0.01% | 0.3% |
| N4000-13EP / EPSI | 0.14% | 0.01% | 0.09% |
| N4000-29 | 0.10% | 0.01% | 0.08% |
| N5000 | 0.25% | 0.001% | 0.23% |
| N7000-1 | 0.34% | 0.02% | 0.34% |
| N7000-2HT / 3 | 0.47% | 0.01% | 0.34% |
| N7000-2V0 | 0.59% | 0.05% | 0.48% |
| N8000 | 0.019% | 0.008% | 0.17% |
| NX9000 | 0.007% | 0% | 0.02% |
| NY9000 | 0.004% | 0% | 0.02% |
| Mercurywave™ 9350 | 0.08% | 0.005% | 0.04% |